



**High quality customer service,
cost effective lobby cash dispenser**

Features

- **Powerful performance**
Powered by Windows XP platform and Pentium processor, it delivers large volume of transaction and high quality service.
Open architecture software meets 15" Color TFT LCD
- **Improved security**
It can satisfy regulatory requirements for on-premise needs including UL291 Level 1 safe, VISA/PCI Encrypting Pin Pad certified, and ADA accessibility.
- **User friendly display**
15" color LCD with touch screen provides attractive interface.
With its privacy filter it assures secure transaction.
- **Enhanced marketing power**
Through high brightness VFD(Vacuum Fluorescent Display), bank can promote their own advertisement. It has superior visibility at a distance and gives a lasting impression to customers.
- **Small footprint, flexible installation**
Monimax 5100 can be installed for both on-premise and off-premise.
Small footprint can allow flexibility for the installation and accessibility for the maintenance.



*Create your true ATM values
Design your own ATM portfolio*



Monimax 5100 is designed to create the optimal effect in both on-premise and off-premise environments. With minor adjustment in software, *Monimax 5100* can support various kinds of value added functions with reduced time and expense for upgrading. Bank's brand is promoted by attaching the CI and distinctive VFD giving it a more stylish and high visibility.

System Control

Intel® Pentium® Processor
Microsoft® Windows XP® platform

Communication

TCP/IP

Optional

Dial-up

Application Software

NDC+, DDC912

Customer Display

15.1" TFT LCD
Actual privacy filter

Input Type

Touch screen
4 x 4 Numeric keys
VISA/PCI EPP(Encrypting PIN pad)
ADA compliant

Card Handling

Dip type card reader

Optional

IC card reader
EMV Level 1, 2

Cash Dispensing

2000 notes cassette
(Up to 4 Cassettes)
200 notes reject bin

Optional

Automatic shutter

Printers

Graphical thermal receipt printer

Security

UL291 Level 1
Electronic safe lock

Optional

Dual safe lock(Dial and key lock)
KABA Mas Cencon safe lock
Security camera

Miscellaneous

Electronic journal

Optional

Heater
VFD(Vacuum Fluorescent Display)

Power Supply

AC 110 ~ 230V, 50~60Hz

Operating Environment

Temperature
32°F ~ 104°F (0°C ~ 40°C)

Optional

14°F ~ 104°F (-10°C ~ 40°C)
Humidity
25% ~ 86%

Dimension and Weight

Height : 61.1" (1552mm)
Width : 18.1" (460mm)
Depth : 30.7" (780mm)
Weight : 694lbs (315kg)

※ New technologies and components may be implemented in the products without prior notice, so Nautilus Hyosung reserves the right to change specifications accordingly.

