

Features

- **Future-trend design**

Innovative design attracts customers' attention with elegant exterior and ease-to-use ergonomic interface. 15" TFT LCD provides unsurpassed convenience to customers and the Vacuum Fluorescent Display (VFD) maximizes advertising effect.

Monimax 5600 features superior and cost-effective performance that outshines all of its competitors.

- **Reliability**

Monimax 5600 guarantees enhanced security with compliance to UL291 Level 1, to EMV Level 1, 2 and surveillance camera.

- **Non-stop operation**

With high-capacity receipt journal and cassettes,

Monimax 5600 can be deployed both on and off premise conditions.



*Create your true ATM values
Design your own ATM portfolio*



Monimax 5600 features superior and reliable performance with various functions including cash withdrawal, card retraction, receipt printing and dot-matrix journal printing or electronic journal. Especially, its modular design guarantees convenient maintenance and unit replacement, and enables

Monimax 5600 to be adjusted according to all requirements customers may need, and its superior Cash Dispensing Unit reduces transaction time and minimizes downtime.

Monimax 5600 can be equipped with up to 4 cassettes.

System Control

Intel® Pentium® Processor
Microsoft® Windows® XP platform

Communication

TCP/IP

Optional

Dial-up, Wireless connection

Application Software

NDC+, DDC912

Customer Display

15" Color TFT LCD
Actual privacy filter

Input Type

4 x 2 Function keys
4 x 4 Numeric keys
VISA/PCI EPP(Encrypting PIN pad)
T-DES
ADA compliant

Optional

Touch screen

Card Handling

Dip type card reader

Optional

IC card reader
EMV Level 1, 2

Cash Dispensing

3000 notes cassette
(up to 4 Cassettes)
Bundle retraction

Printers

Graphical thermal receipt printer

Optional

Journal printer

Security

UL291 Level 1
Electronic safe lock
Security camera

Optional

KABA Mas Cencon lock

Miscellaneous

Lead-through indicator

Optional

Heater
VFD(Vacuum Fluorescent Display)

Power Supply

AC 110 ~ 230V, 50~60Hz

Operating Environment

Temperature
32°F ~ 104°F (0°C ~ 40°C)

Optional

14°F ~ 104°F (-10°C ~ 40°C)

Humidity

25% ~ 86%

Dimension and Weight

Height : 59.3"(1,505mm)

Width : 18.5"(470mm)

Depth : 29.9"(760mm)

Weight : 978lbs (444kg)

(when UL291 Level 1 safe)

※ New technologies and components may be implemented in the products without prior notice, so Nautilus Hyosung reserves the right to change specifications accordingly.

