



## SPECIFICATIONS

### Dimensions

Machine: 31.5" H 20" W 28.5" D  
 Facia: 33" H 23.75" W  
 Weight: 283 lbs

Minimum hole size: 31.5" H 20" W  
 Wall thickness: 4" - 10"

### Operating Environment

Temperature range: 40°F - 95°F (operating)  
 Relative humidity: 15% - 85% (NC)  
 Electrical: 110VAC - 230VAC

56K modem for dial-up CSP200 emulation  
 1MB of memory  
 Utility software available for graphics download

### Security

UL 291 business hour vault  
 Triple DES with lab certified Encrypting PIN Pad (EPP)

### Compliance

Triple DES compliant  
 Voice guidance standard

### Options

Rear service panel  
 Dial or Cencon Series electronic lock

2100T

# Mini-Bank 2100T Series

the affordable  
retail through-the-wall



## OPERATIONAL SERVICES



Tranax makes your ATM ownership experience as easy as possible.

**WebRMS** is a web-based monitoring and cash management solution that ensures a reliable network of ATMs. Instant alerts on your cell phone and via email, as well as online access to electronic journal records, allow you to monitor the health of your ATMs 24/7. WebRMS increases your ATMs' uptime and lowers your operational costs.

**Tranax Extend** offers ATM owners a worry-free investment in a Tranax ATM beyond the standard manufacturer's warranty. If a component of an ATM covered under Extend is in need of repair, Tranax will promptly ship a working replacement part at no charge.

For more information please call 1.888.340.2484 or visit us at [www.tranax.com](http://www.tranax.com)

Tranax® and the Tranax logo are trademarks of Tranax Technologies, Incorporated. © 2005 Tranax Technologies, Incorporated. Specifications subject to change without notice. Tranax endeavors to ensure that the information in this document is correct and fairly stated but does not accept liability for any error or omissions.

# Discover the Tranax Mini-Bank 2100T™

The **Mini-Bank 2100T** now offers retail locations an economical through-the-wall ATM solution. Designed around a robust yet compact architecture, the unit offers a high degree of **flexibility for installation** and mounting. Utilizing field-proven components found in many other Tranax retail ATMs, including the receipt printer, cash dispenser and CPU, this unit offers a **weatherized** construction.

The Mini-Bank 2100T retains the **reliability and low maintenance** you've come to expect from Tranax, featuring a standard 2000 note capacity cassette, optional rear service panel, and **sun-viewable LCD**. With the look and feel of a bank machine at the **cost of a retail ATM**, the Mini-Bank 2100T meets all regulatory guidelines including full **Triple DES compliance**, a **VISA Lab Certified Encrypting PIN Pad** and ADA compliant voice guidance system as standard.

# Mini-Bank 2100T Series



**SIGNAGE**  
Lighted top panel can be branded with adhesive logos or signs

**SCREEN**  
5.7 " Monochrome Transreflective LCD display features 8 function keys and a 6 screen advertisement capability

**WEATHERIZED**  
Covered cash-tray and water resistant keypad, printer and screen ensure reliable operation in all climates

**ADA**  
Americans with Disabilities Act (ADA) compliant voice guidance system

**KEYPAD**  
VISA lab certified, TDES compliant 16-key alphanumeric keypad



**PRINTER**  
3 1/8" thermal printer with auto paper loading and cutting, accommodates a 7" paper roll and slides out for easy service

**SECURITY / SERVICABILITY**  
Vault is contained separately from the serviceable components allowing access for technicians without opening the vault

**CASH DISPENSER**  
Proven Mini-Bank 2100T series dispenser with locking reject bin and 2000 note cassette, slides out easily for service access



**SERVICE PANEL**  
Optional service panel allows monitoring, configuration, diagnostics and maintenance.