# Mini-Bank

# NH-2100T



The Best Value in retail through-the-wall ATM, the NH-2100T offers flexibility for installation with its efficient design

## **Features**

### Reliability

NH-2100T meets security standards such as Triple DES compliance and a VISA Encrypting PIN pad. Transreflective LCD display and weatherized construction ensures operation in all climates.

### Flexibility

Compact architecture with ergonomic design offers unrivalled flexibility for installation and mounting in all environments.



# Create your true ATM values Design your own portfolio



The **NH-2100T** provides outstanding flexibility and reliability to satisfy your requirements.

The **NH-2100T** supports exceptional reliable performance with various components such as standard 2000 note capacity cash dispenser and service panel for monitoring, configuration, diagnostics and maintenance.

Our solution strengthens you to build better customer relationships as well as enhanced technologies



## Mini-Bank

# NH -2100 T



#### **Customer Display**

5.7" Monochrome Transreflective LCD

#### **Communication**

Dial-up

#### **Optional**

TCP/IP

#### Input Type

4 x 2 Function keys

4 x 4 Numeric keys

**Encrypting PIN Pad** 

(DES,T-DES, Unique Key)

#### Supervisor Operation

Customer display in common

#### **Optional**

Service panel

5.7" mono display

4 x 2 function keys, 16keys

#### **Card Handling**

Dip type card reader

#### **Optional**

IC card reader

#### Cash Dispensing

2000 note cassette 200 notes reject bin

#### **Printers**

Thermal receipt printer

#### Security

UL291 business hour vault Dial Lock

#### **Optional**

Electronic Safe Lock KABA Mas Cencon Safe Lock

#### Miscellaneous

Illuminated signage

#### **Optional**

Adjustable pedestal

#### **Power Supply**

AC 110~230V, 50~60Hz

#### **Operating Environment**

Temperature

40°F~95°F (5°C ~ 35°C)

Humidity

15%~85%

#### Dimension and Weight

Height: 31.5" (800mm) Width: 20" (508mm)

Depth: 28.5" (724mm) Weight: 283 lbs (128kg) Wall thickness: 4" ~ 10"

\* New technologies and components may be implemented in the products without prior notice, so Nautilus Hyosung reserve the right to change specifications accordingly.



Head office) 52 Cheongdam-Dong, Gangnam-Gu, Seoul, Korea 135-100

TEL:+82-2-510-0441, FAX:+82-2-3442-7993, http://www.nautilus.hyosung.com

US office)

William Square Center #218, 5205 North O'CONNER Blvd, Irving, TX 75039 TEL:972-443-9820, FAX:972-443-9821

